
Adhesive 2000

Shaw 2000

DESCRIPTION: 2000 PREMIUM CARPET ADHESIVE

is a latex-based adhesive specially formulated for difficult to hold backing. May be used to install a wide range of carpet and resilient floor coverings, except those with vinyl backs. #2000 offers a quick grab, aggressive tack, and a strong permanent bond.

INSTALLATION:

Carpet Installation – For most carpets and/or porous surfaces use a 1/8"x1/16"x1/8" V-notch trowel. The carpet should be installed in most cases within 20 minutes after the adhesive application. Approximately 30 minutes after installation, the carpet should be rolled with a 30-50 lb. carpet roller.

Sheet Good Installation – Apply adhesive using a 1/16"x1/16"x1/16" Square-Notch trowel for sheet goods. The sheet goods should be installed within 20 minutes after the application of the adhesive. After the installation of the sheet goods, the floor should be rolled with a 75 lb. roller.

PHYSICAL PROPERTIES:

V.O.C.:	0 grams per liter (calculated)
Base:	Synthetic rubber
Solids:	60%
Color:	Off white
Consistency:	Smooth, easy-to-spread mastic
Shelf Life:	Up to one year at 65°F in unopened container.
Flammability:	Qualified for NFPA Class A and UBC Class I fire ratings as determined by the ASTM E84 tunnel test. Conforms to the requirements of the Hill-Burton test.
Clean-Up:	Use warm, soapy water while the adhesive is still wet. If dried, use non-flammable safety solvent.

CAUTION:

Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately.

WARRANTY:

This adhesive is manufactured according to exacting quality standards and warranted to be free from manufacturing defects. Defective material called to our attention within one year from manufacture will be replaced. No guarantee, expressed or implied is made regarding the performance of this product since the manner and conditions are beyond our control.

Material Safety Data Sheet

IDENTITY (As shown on label):

Shaw 2000 Premium Carpet Adhesive

SECTION I

Prepared by: Todd Bethel

Manufacturer Name: Shaw Industries, Inc.

Address/Phone: P.O. Drawer 2128; Dalton, Ga 30722; (800)441-7429

Emergency Telephone No.: (800)535-5053

Product Class: Synthetic rubber, resin blend

Manufacturer's Code Identification: 2000

Trade Name: Premium Carpet Adhesive

SECTION II

HAZARDOUS INGREDIENTS

SARA Title III Section 313 Chemicals: Methanol

SECTION III

PHYSICAL DATA

LBS/GAL: 9.5-10.0

Evaporation Rate: Same as water

Vapor Density: Same as water

Vapor Pressure: Same as water

Percent Volatile by volume: 40 (by weight) \pm 2%

Color: Off White

Odor: NIL

Grams V.O.C. per liter of material: 0 (calculated)

Grams V.O.C. per liter of coating: 0 (calculated)

SECTION IV

FIRE & EXPLOSION HAZARD DATA

Dot Category: Not regulated

Flash Point: None

LEL: N/A

Extinguishing Media: None required

Unusual Fire & Explosion Hazards: None known

Special Fire Fighting Procedures: None

SECTION V

HEALTH HAZARD DATA SYMPTOMS OF OVER EXPOSURE

Inhalation: None known

Ingestion: None known

Skin: None known

Eyes: May cause mild irritation

SECTION VI

REACTIVITY DATA

Stability: Stable

Conditions to avoid: None known

Incompatibility-Materials to Avoid: None known

Hazardous decomposition products: None known

Hazardous polymerization: Will not occur

SECTION VII

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED.

Use absorbent material to collect and contain for salvage or disposal.

Waste Disposal: Abide by all state, federal, and local regulations.

SECTION VIII

SPECIAL PROTECTION INFORMATION

Respiratory Protection: Wear NIOSH respiratory protection if above TLV

Eyes: Goggles

Ventilation: Local exhaust – none should be needed

Protective Gloves: None required

Other Protective Equipment: None

SECTION IX

SPECIAL PRECAUTIONS

Precaution for handling and storing: Do not puncture

KEEP OUT OF THE REACH OF CHILDREN.