
Adhesive 2001

Shaw 2001

DESCRIPTION: 2001 PREMIUM CARPET ADHESIVE

is a synthetic latex-based adhesive specially formulated for the installations of direct glue down carpets. #2001 is recommended to install a wide range of carpet backings except those with vinyl backs. #2001 offers a long working time with aggressive grab and a strong permanent bond. #2001 is not recommended for non-porous backed carpets, patterned carpet installations, or carpet to cushion in a double stick installation.

INSTALLATION:

For most carpets and/or porous substrates use a 1/8" width x 1/18" depth x 1/16" spacing V-notch trowel. Allow a 15-minute open time to allow the adhesive to start to develop "legs" before installing carpet. Seal all seams using Shaw 4000 Seam Sealer. When installation is complete roll and cross roll using a 50-75 lb. roller.

PHYSICAL PROPERTIES:

V.O.C.:	0 grams per liter (calculated)
Base:	Synthetic rubber
Solids:	60%
Color:	Off white
Consistency:	Smooth, easy-to-spread
Shelf Life:	Up to one year at 65°F in unopened container.
Flammability:	Qualified for NFPA Class A and UBC Class I fire ratings as determined by the ASTM E84 tunnel test. Conforms to the requirements of the Hill-Burton test.
Clean-Up:	Use warm, soapy water while the adhesive is still wet. If dried, use non-flammable safety solvent.

CAUTION:

Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately.

WARRANTY:

Our only obligation shall be to replace or pay for any adhesive proved defective. Beyond the purchase price of materials supplied by us, we assume no liability for

direct, indirect, or consequential damages of any kind, and the use accepts the product "as is" and without warranties, expressed or implied. The suitability of the product for an intended use shall be solely up to the user. Shelf life is one year from the manufacturing date according to the batch lot number on each container. Registered trademark of respective manufacturer. For additional MSDS information contact Shaw Industries, Inc. at 1-800-441-7429.

Material Safety Data Sheet

IDENTITY (As shown on label):

Shaw 2001 Premium Carpet Adhesive

SECTION I

Prepared by: Todd Bethel

Manufacturer Name: Shaw Industries, Inc.

Address/Phone: P.O. Drawer 2128; Dalton, Ga 30722; (800)441-7429

Emergency Telephone No.: (800)535-5053

Product Class: Synthetic rubber, resin blend

Manufacturer's Code Identification: 2001

Trade Name: Premium Carpet Adhesive

SECTION II

HAZARDOUS INGREDIENTS

None per OSHA Regulation: 29 CFR 1910.1200

SARA Title III Section 313 Chemicals: None

SECTION III

PHYSICAL DATA

LBS/GAL: 9.5-10.0

Evaporation Rate: Same as water

Vapor Density: Same as water

Vapor Pressure: Same as water

Percent Volatile by volume: 40-42%

Color: Off White

Odor: NIL

Grams V.O.C. per liter of material: 0 (calculated)

Grams V.O.C. per liter of coating: 0 (calculated)

SECTION IV

FIRE & EXPLOSION HAZARD DATA

Dot Category: Not regulated

Flash Point: None

LEL: N/A

Extinguishing Media: None required

Unusual Fire & Explosion Hazards: None known

Special Fire Fighting Procedures: None

SECTION V

HEALTH HAZARD DATA SYMPTOMS OF OVER EXPOSURE

Inhalation: None known

Ingestion: None known

Skin: None known

Eyes: May cause mild irritation

SECTION VI

REACTIVITY DATA

Stability: Stable

Conditions to avoid: None known

Incompatibility-Materials to Avoid: None known

Hazardous decomposition products: None known

Hazardous polymerization: Will not occur

SECTION VII

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED.

Use absorbent material to collect and contain for salvage or disposal.

Waste Disposal: Abide by all state, federal, and local regulations.

SECTION VIII

SPECIAL PROTECTION INFORMATION

Respiratory Protection: Wear NIOSH respiratory protection if above TLV

Eyes: Goggles

Ventilation: Local exhaust – none should be needed

Protective Gloves: None required

Other Protective Equipment: None

SECTION IX

SPECIAL PRECAUTIONS

Precaution for handling and storing: Do not puncture

KEEP OUT OF THE REACH OF CHILDREN.