

## Adhesive 3000

**Shaw 3000****DESCRIPTION: 3000 RESILIENT FLOORING ADHESIVE**

is a white, non-staining, solvent-free, low odor adhesive made for the installation of all brands of resilient sheetgoods, except those with a vinyl backing. Use over plywood, hardboard, lining felt, concrete, and terrazzo. Extensive lab tests show that #3000 will not contribute to discoloration of new stain-sensitive paperback and "Mineral-back" sheetgoods designed for conventional, full spread installation. While it will not cause staining or discoloration, it cannot prevent discoloration from other sources such as air, ultraviolet rays, tannin (present in Western Cedar), spills, dyes, and other chemicals or from the inherent instability of the floor covering.

**APPLICATION:**

Apply adhesive with a trowel notched to leave ample adhesive on the floor for the job conditions. Suggested trowel notch size for sheetgoods is 1/16"x1/16"x1/16" Square-notch. Prime all acoustical concrete floors. Skim coat (with a smooth trowel) all very porous wood and concrete floors with this adhesive before the main coat is applied. Work from the center toward the edges to expel any trapped air and to ensure good bonding.

**PHYSICAL PROPERTIES:**

V.O.C.:	0 grams per liter (calculated)
Base:	Synthetic latex
Solids:	54%
Color:	White
Consistency:	Smooth, easy-to-spread
Open Time:	None
Shelf Life:	Up to one year at 70°F in unopened container.
Flammability:	Qualified for NFPA Class A and UBC Class I fire ratings as determined by the ASTM E84 tunnel test. Conforms to the requirements of the Hill-Burton test.
Other Features:	Freeze thaw stable. Mildew-proof. Odorless when dry. Water resistant when dry and cure

**CAUTION:**

Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately.

**WARRANTY:**

This adhesive is manufactured according to exacting quality standards and warranted to be free from manufacturing defects. Defective material called to our attention within one year from manufacture will be replaced. No guarantee, expressed or implied is made regarding the performance of this product since the manner and conditions are beyond our control.

**Material Safety Data Sheet****IDENTITY (As shown on label):**

Shaw 3000 Resilient Flooring Adhesive

**SECTION I**

**Prepared by:** Todd Bethel

**Manufacturer Name:** Shaw Industries, Inc.

**Address/Phone:** P.O. Drawer 2128; Dalton, Ga 30722; (800)441-7429

**Emergency Telephone No.:** (800)535-5053

**Product Class:** Synthetic rubber, resin blend

**Manufacturer's Code Identification:** 3000

**Trade Name:** Resilient Flooring Adhesive

**SECTION II****HAZARDOUS INGREDIENTS**

**None per OSHA Regulation:** 29 CFR 1910.1200

**SARA Title III Section 313 Chemicals:** None

**SECTION III****PHYSICAL DATA**

**Boiling Point:** 212°F

**LBS/GAL:** 9-10

**Evaporation Rate:** Same as water

**Vapor Density:** Same as water

**Vapor Pressure:** Same as water

**Percent Volatile by volume:** 40-50% (by weight)

**Color:** White

**Odor:** NIL

**Grams V.O.C. per liter of material:** 0 (calculated)

**Grams V.O.C. per liter of coating:** 0 (calculated)

**SECTION IV****FIRE & EXPLOSION HAZARD DATA**

**Dot Category:** Not regulated  
**Flash Point:** None  
**LEL:** N/A  
**Extinguishing Media:** Non-flammable  
**Unusual Fire & Explosion Hazards:** None known  
**Special Fire Fighting Procedures:** None known

## **SECTION V**

### **HEALTH HAZARD DATA SYMPTOMS OF OVER EXPOSURE**

**Inhalation:** None known  
**Ingestion:** None known  
**Skin:** None known  
**Eyes:** May cause mild irritation

### **FIRST AID PROCEDURES**

**Eyes:** Flush with water  
**Skin:** Wash with soap and water  
**Inhalation:** Remove to fresh air if needed

## **SECTION VI**

### **REACTIVITY DATA**

**Stability:** Stable  
**Conditions to avoid:** None known  
**Incompatibility-Materials to Avoid:** None known  
**Hazardous decomposition products:** None known  
**Hazardous polymerization:** Will not occur

## **SECTION VII**

### **SPILL OR LEAK PROCEDURES**

#### **STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED.**

Use absorbent material to collect and contain for salvage or disposal.  
**Waste Disposal:** Abide by all state, federal, and local regulations.

## **SECTION VIII**

### **SPECIAL PROTECTION INFORMATION**

**Respiratory Protection:** None should be needed  
**Eyes:** Goggles  
**Ventilation:** Local exhaust  
**Protective Gloves:** None required  
**Other Protective Equipment:** None

**SECTION IX**

**SPECIAL PRECAUTIONS**

**Precaution for handling and storing:** Do not puncture

**KEEP OUT OF THE REACH OF CHILDREN.**

**Freeze thaw stable at 10°F**