

## Adhesive 4030

**Shaw 4030****DESCRIPTION: 4030 VINYL COMPOSITION TILE  
ADHESIVE**

is a fast drying, high tack adhesive made for the installation of vinyl composition tile, asphalt tile, closed cell foam back hardwood parquet, non-vinyl backed sheetgoods and carpet. May be sprayed, brushed, troweled, or rolled over plywood, terrazzo, concrete, or existing VCT. #4030 will not contribute to adhesive induced staining. Maintains excellent water resistance.

**APPLICATION:**

Plan and lay out the installation before spreading the adhesive. Apply adhesive with a short-napped roller, brush, or 1/16"x1/16"x1/16" square-notched trowel. Let adhesive dry to a clear tacky state before laying tiles. When tiles have been laid, roll and cross roll with a 75 or 100 pound linoleum roller. Follow all label instructions before installing.

**PHYSICAL PROPERTIES:**

V.O.C.:	0 grams per liter (calculated)
Base:	Synthetic latex
Solids:	53%
Color:	Cream, dries transparent
Consistency:	Light paste
Open Time:	Long residual tack time up to 48 hours
Shelf Life:	Up to one year at 70°F in unopened container.
Coverage:	Up to 180 – 250 sq. ft. per gallon
Flammability:	Non-flammable, qualified for NFPA Class A and UBC Class I fire ratings determined by the ASTM E84 Tunnel Test. Conforms to the requirements of the Hill-Burton Act.
Clean-Up:	Use warm, soapy water while adhesive is still wet.

**CAUTION:**

Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately.

**WARRANTY:**

This adhesive is manufactured according to exacting quality standards and warranted to be free from manufacturing defects. Defective material called to our attention within one year from manufacture will be replaced. No guarantee, expressed or implied is made regarding the performance of this product since the manner and conditions are beyond our control.

## **Material Safety Data Sheet**

### **IDENTITY (As shown on label):**

Shaw 4030 Vinyl Composition Tile Adhesive

#### **SECTION I**

**Prepared by:** Todd Bethel

**Manufacturer Name:** Shaw Industries, Inc.

**Address/Phone:** P.O. Drawer 2128; Dalton, Ga 30722; (800)441-7429

**Emergency Telephone No.:** (800)535-5053

**Product Class:** Synthetic rubber, resin blend

**Manufacturer's Code Identification:** 4030

**Trade Name:** Vinyl Composition Tile Adhesive

#### **SECTION II**

##### **HAZARDOUS INGREDIENTS**

**None per OSHA Regulation:** 29 CFR 1910.1200

**SARA Title III Section 313 Chemicals:** None

#### **SECTION III**

##### **PHYSICAL DATA**

**Boiling Point:** 212°F

**LBS/GAL:** 8.3

**Evaporation Rate:** Same as water

**Vapor Density:** Same as water

**Vapor Pressure:** Same as water

**Percent Volatile by volume:** 40-50% (by weight)

**Color:** Off White

**Odor:** Slight ammonia-like odor

**Grams V.O.C. per liter of material:** 0 (calculated)

**Grams V.O.C. per liter of coating:** 0 (calculated)

#### **SECTION IV**

##### **FIRE & EXPLOSION HAZARD DATA**

**Dot Category:** Not regulated

**Flash Point:** None

LEL: N/A

**Extinguishing Media:** Non-flammable

**Unusual Fire & Explosion Hazards:** None known

**Special Fire Fighting Procedures:** None known

## **SECTION V**

### **HEALTH HAZARD DATA SYMPTOMS OF OVER EXPOSURE**

**Inhalation:** None known

**Ingestion:** None known

**Skin:** None known

**Eyes:** May cause mild irritation

### **FIRST AID PROCEDURES**

**Eyes:** Flush with water

**Skin:** Wash with soap and water

**Inhalation:** Remove to fresh air if needed

## **SECTION VI**

### **REACTIVITY DATA**

**Stability:** Stable

**Conditions to avoid:** None known

**Incompatibility-Materials to Avoid:** None known

**Hazardous decomposition products:** None known

**Hazardous polymerization:** Will not occur

## **SECTION VII**

### **SPILL OR LEAK PROCEDURES**

#### **STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED.**

Use absorbent material to collect and contain for salvage or disposal.

**Waste Disposal:** Abide by all state, federal, and local regulations.

## **SECTION VIII**

### **SPECIAL PROTECTION INFORMATION**

**Respiratory Protection:** None should be needed

**Eyes:** Goggles

**Ventilation:** Local exhaust

**Protective Gloves:** None required

**Other Protective Equipment:** None

## **SECTION IX**

### **SPECIAL PRECAUTIONS**

**Precaution for handling and storing:** Do not puncture



**KEEP OUT OF THE REACH OF CHILDREN.**