

Adhesive 6001

Shaw 6001**DESCRIPTION: SHAW SURESET 6001 VINYL BACK CARPET SEAM ADHESIVE**

provides a polymer fortified adhesive bond and is recommended for seaming all vinyl back carpets.

APPLICATION:

Prepare carpet according to manufacturer's instructions. Apply a bead of sealer along the carpet vinyl edge with an adhesive applicator bottle. Apply adhesive to only one side of carpet. Complete the seam by butting both sections of the carpet together while the adhesive is still wet (within 5-10 minutes). If the sealer thickens, add a little water and stir. This will reduce the consistency and make it easy to apply. Smears of sealer on the carpet surface are easily cleaned within 10 minutes of rubbing with a clean cloth wet with soapy water. Avoid soaking carpet with water. Do not pour soapy water directly on carpet.

PHYSICAL PROPERTIES:

V.O.C.:	0 (calculated)
Base:	Latex/polymer mixture
Color:	Cream colored liquid
Flammability:	Non-flammable
Clean-Up:	Use warm, soapy water.

CAUTION:

Use with sufficient ventilation. Prevent prolonged or repeated breathing of vapors or mist. Use fans, motors and other equipment, open doors and windows as necessary. Do not use in confined areas without proper ventilation. Keep container closed when not in use. Vapors, while low in toxicity, are capable of causing fainting.

WARRANTY:

Shaw Industries, Inc.'s only obligation shall be to replace or pay for any adhesive proved defective. Beyond the purchase price of materials supplied by us, we assume no liability for direct, indirect or consequential damages of any kind, and

the user accepts the product for particular purpose or intended use shall be solely up to the user.

Material Safety Data Sheet

IDENTITY (As shown on label):

Shaw SureSet 6001

SECTION I

Prepared by: Todd Bethel

Manufacturer Name: Shaw Industries, Inc.

Address/Phone: P.O. Drawer 2128; Dalton, Ga 30722; (800)441-7429

Emergency Telephone No.: (800)535-5053

Manufacturer's Code Identification: 6001

Trade Name: Vinyl Back Carpet Seam Sealer

SECTION II

HAZARDOUS INGREDIENTS

None per OSHA Regulation: 29 CFR 1910.1200

SARA Title III Section 313 Chemicals: None

SECTION III

PHYSICAL DATA

Boiling Point: 212°F

Vapor Density (Air=1): >1

Evaporation Rate N-Butyl Acetate =1): Same as water

Vapor Pressure (mmHG at 20c): Same as water

Color: Cream colored

Odor: Slight ammonia-like odor

SECTION IV

FIRE & EXPLOSION HAZARD DATA

Flash Point, Pensky-Marens C.C: N/A

Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical

Unusual Fire & Explosion Hazards: None known

Special Fire Fighting Procedures: Wear self-contained breathing apparatus

SECTION V

HEALTH HAZARD DATA SYMPTOMS OF OVER EXPOSURE

Inhalation: May cause irritation

Ingestion: Not a likely route of entry under proper handling conditions

Skin: May cause slight irritation

Eyes: May cause slight eye irritation

FIRST AID PROCEDURES

Eyes: Flush with water

Skin: Wash with soap and water

Inhalation: Remove to fresh air if needed

SECTION VI

REACTIVITY DATA

Stability: Stable

Conditions to avoid: Protect from freezing

Hazardous decomposition products: Oxides of carbon, water and organic compounds of unknown structure

Hazardous polymerization: Will not occur

SECTION VII

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED.

Keep out of sewer systems to prevent blockage due to polymer deposits. Soak up materials with absorbent material and place into closed containers.

Waste Disposal: Abide by all state, federal, and local regulations.

SECTION VIII

SPECIAL PROTECTION INFORMATION

Respiratory Protection: None should be needed

Eyes: Chemical Goggles

Ventilation: Local exhaust

Protective Gloves: Chemical resistant

Other Protective Equipment: None

SECTION IX

SPECIAL PRECAUTIONS

Precaution for handling and storing: Use with adequate ventilation. Protect from freezing.

KEEP OUT OF THE REACH OF CHILDREN.