

## Installation Specifications for Shaw Carpet Backing Systems

Backing Application		Recommended Installation		Method	Shaw 2057	Shaw 1000	Shaw 5000	Trowel Sizes	Spread Rate Yds/Gal	Cutting Techniques	Seam Sealer 1 Quart	Shaw Advantage System
		Direct Glue	Double Glue		Stretch - In	Patterned Adhesive	Multi Purpose					Pressure Sensitive
Double Stick	Pad to Floor					X		3/32 x 3/32 x 3/32 V	10-12			
Double Stick w/DuraTech V Plus Pad Only	Cpt to Pad					X		1/8 x 1/8 x 1/16 U	4-8	Row cut / Row cut	Shaw 4000	
Actionbac / Softbac		X	X	X *	X	X		1/8 x1/8 x 1/8 U	8-10	Row cut / Row cut	Shaw 4000	X
Actionbac PC / LXT-EX4-TR18 / Kanga		X			X	X		1/8 x1/8 x 1/8 U	8-10	Row cut / Row cut	Shaw 4000	
The Enhancer - Stalok Cushion / Ultraloc MPC / Everbond EC		X			X	X		1/8 x1/8 x 1/8 U	8-10	5 degree bevel (a) Row Cut/Row Cut	Shaw 4000	
Stalok - Enforcer / Ultraloc MP / Everbond EL		X	X		X	X		1/8 x1/8 x 1/8 U	8-10	Row Cut/Row Cut	Shaw 4000	X
Unitary / Certilok		X				X		1/8 x1/8 x 1/8 U	8-10	Row Cut/Trace Cut	Shaw 4000	
Unitary/Actionbac / Teklok / Ultraloc Pattern / Everbond EX / EX2 / A2 / Double Lock Unitary /Stalok Pattern / Stalok AB		X	X	X *	X	X		1/8 x1/8 x 1/8 U	8-10	Row Cut/Row Cut	Shaw 4000	X
Ecworx 6		X					X	1/16 x 1/16 x 1/16 V	20	Row cut / Trace cut	Shaw 8300	Exception Sports Stripe
Ecworx Sq.		X					X	3/8 foam paint roller	35-40	Use Straight Edge	n/a	X

Adhesives are in 4 gallon pails, 48 pails per pallet, 35 lbs. per pail.

Seam Sealer Spread Rates - Shaw 4000 approximately 550-600 Linear Ft. per Quart using a 1/8 inch bead, 12 quarts per case. Shaw 8300 approximately 138-150 Linear Ft. per 8oz. Bottle using a 1/16 inch bead, 12 / 8oz. bottles per case.

Floorshield 9000 - Floor sealer for unknown or incompatible adhesives such as asbestos or asphaltic adhesives (Cutback). Spread rate for the Floorshield 9000 is approximately 27 to 30 yards per gallon and contains 2.5 gallons per container.

9050 Shaw Floor Sealer: 4 gallon, 48 pails per pallet. Spread rate: 350-500 sq. ft. per gallon.

Line material for Sports Floor: Regular Basketball Court 6 x 30, add 6 x 15 for 3 point lines, and 6 x 12 for Volleyball.

Sports Floor Tool Kit: Radius Cutter and Gripper Plate. Style #00048, Code 820.

**\* Note - All Stretch-In installation should not exceed 35 feet in width and length in order to achieve an adequate stretch.**

Advantage System - 40"W x 150"L - Coverage approximately 55.5 Sq. yds. Approximately 33 lbs. in weight. Advantage System Styles AVSTR, AVSCC, AVNET and AVPHI. Not for all backing systems or patterned styles.

Advantage System Perimeter Tape - Broadloom Only. Use only when cove base is not used. Approximately 60 ft per roll and 9 rolls per case. 5 inches in width. Advantage Systems Styles DFSCC and DFSTR.

\*Installation bulletins are available on request. Call 1-800-471-7429 to obtain the most current bulletin number. Manufacturing is subject to change formulations of our products. Please refer to all manufacturer's suggested use and precautions.

Shaw Industries, Inc., Technical Services Department Bulletin #C130-012805